

4 Port Video Encoder

Leverage Existing Analog Video Infrastructure
While Transitioning to IP-Based Systems

Each IP Video Encoder Blade comes bundled with a 4-camera license for our enterprise class IP Video Surveillance software



VE4-IPsv4

Technical Specifications

Inputs	4 BNC inputs
IP Licenses	4 Cameras
Output - Single Stream	1 Quad Output
Output - Dual Stream	2 Loop Out
Compression Type	MPEG-4, MJPEG Selectable
Resolutions	D1, 2 CIF, CIF, QCIF
FPS	100 / 120 fps @ D1
De-interlacing	Hardware Encoding Engine
Compression	G.711
PTZ Support	RS - 422 / 485
Protocols	TCP/IP, UDP/IP, HTTP, RTSP, RTCP, RTP/UDP, RTP/TCP, SNMP, mDNS, UPnP, SMTP, Sock, IGMP, DHCP, FTP, DDNS, PPPoE
Networking	10 / 100 Base T
Weight	1.5 lbs
Dimensions	5.4" (w) x 1.5" (h) x 3.4" X 7.2" (d)
Temperature Range	0 degrees C - 60 degrees C (32 degrees F - 140 degrees F)
Humidity	Up to 85% RH (Non-condensing)
Power Inputs	12vDC (DC Jack)
PoE Support	Support (IEEE 802.3af, Optional)
Power Usage	848 mA @ 12V

Video Insight, Inc.
3 Riverway, Suite 700
Houston, TX 77056
713-621-9779
www.video-insight.com
sales@video-insight.com